

WASTE STREAM	7D40 ILW PCD Ion Exchange Resin
---------------------	--

SITE HMNB Devonport
SITE OWNER Ministry of Defence
WASTE CUSTODIAN Babcock International Group
WASTE TYPE ILW

WASTE VOLUMES

		Reported
Stocks:	At 1.4.2019.....	10.4 m ³
Future arisings -	1.4.2019 - 31.3.2030.....	0 m ³
Total future arisings:		0 m ³
Total waste volume:		10.4 m ³

Comment on volumes: Dependent upon the submarine maintenance programme. Waste disposal campaign being prepared which is expected to include conditioning/treatment to remove C14 & chelates. Campaign expected to include all other resin waste streams which include C-14 as well as chelate content.

Uncertainty factors on volumes:	Stock (upper):	x 1.4	Arisings (upper)	x
	Stock (lower):	x 0.6	Arisings (lower)	x

WASTE SOURCE The primary circuit of the reactor power plant is decontaminated using a multi-stage chemical process. Resin is used to remove soluble metal activation products that are generated when the magnetite layer is removed from the primary plant.

PHYSICAL CHARACTERISTICS

General description: Ion exchange resin that is headed with an amount of water. The conditioned waste will require to be pre-treated to remove the chelate (and C-14) concentrations and the product will be encapsulated into either drums or other approved containers (e.g. THISO).

Physical components (%wt): Ion exchange resin (75%), water (25%)

Sealed sources: The waste does not contain sealed sources.

Bulk density (t/m³): 1.1

Comment on density: The waste contains organic based ion exchange resin. There are equal numbers of active anion and cation sites. The resin is a polystyrene based bead consisting of uniform spheroids of approximately 1mm diameter. Pre-conditioned resin is always held in a wet state and is 'headed' by a quantity of demineralised water. Due to the chemical decontamination process being used the resin will contain appreciable quantities of chelating agents (>>1 % by weight). There are no large items present. The density will be in the region of 1-1.1 t/m³. Once conditioned for disposal the density will increase as the waste will be encapsulated into an appropriate concrete matrix.

CHEMICAL COMPOSITION

General description and components (%wt): Ion exchange resin (75%), water (25%)

Chemical state: Acid

Chemical form of radionuclides: H-3: Present as HTO in the overstanding water.
C-14: On resin in various chemical forms, mainly adhered to the resin.

Metals and alloys (%wt): -

Stainless steel.....	0
Other ferrous metals.....	0
Iron.....	0
Aluminium.....	0
Beryllium.....	0
Cobalt.....	0
Copper.....	0
Lead.....	0

WASTE STREAM

7D40 ILW PCD Ion Exchange Resin

Magnox/Magnesium..... 0
 Nickel..... 0
 Titanium..... 0
 Uranium..... 0
 Zinc..... 0
 Zircaloy/Zirconium..... 0
 Other metals..... 0

Not applicable apart from the metal activation products that have adhered to the resin. This is in very small concentrations.

Organics (%wt):

-
 Total cellulosics..... 0
 Paper, cotton..... 0
 Wood..... 0
 Halogenated plastics 0
 Total non-halogenated plastics..... 0
 Condensation polymers..... 0
 Others..... 0
 Organic ion exchange materials.... 75.0
 Total rubber..... 0
 Halogenated rubber 0
 Non-halogenated rubber..... 0
 Hydrocarbons.....
 Oil or grease
 Fuel.....
 Asphalt/Tarmac (cont.coal tar)...
 Asphalt/Tarmac (no coal tar)....
 Bitumen.....
 Others.....
 Other organics..... 0

Other materials (%wt):

-
 Inorganic ion exchange materials. 0
 Inorganic sludges and flocs..... 0
 Soil..... 0
 Brick/Stone/Rubble..... 0
 Cementitious material..... 0
 Sand..... 0
 Glass/Ceramics.....
 Graphite..... 0
 Desiccants/Catalysts..... 0
 Asbestos..... 0
 Non/low friable.....
 Moderately friable.....
 Highly friable.....

WASTE STREAM**7D40 ILW PCD Ion Exchange Resin**

	Free aqueous liquids.....	25.0
	Free non-aqueous liquids.....	0
	Powder/Ash.....	0
Inorganic anions (%wt):	It is not expected that there will be a significant amount of inorganic anions within the waste.	
	Fluoride.....	0
	Chloride.....	0
	Iodide.....	0
	Cyanide.....	0
	Carbonate.....	0
	Nitrate.....	0
	Nitrite.....	0
	Phosphate.....	0
	Sulphate.....	0
	Sulphide.....	0
Materials of interest for waste acceptance criteria:	Chelates above the LLWR acceptance criteria which must be removed from the raw waste by a preconditioning process (see 7D34).	
	Combustible metals.....	0
	Low flash point liquids.....	0
	Explosive materials.....	0
	Phosphorus.....	0
	Hydrides.....	0
	Biological etc. materials.....	0
	Biodegradable materials.....	0
	Putrescible wastes.....	0
	Non-putrescible wastes.....	0
	Corrosive materials.....	0
	Pyrophoric materials.....	0
	Generating toxic gases.....	0
	Reacting with water.....	0
	Active particles.....	0
	Soluble solids as bulk chemical compounds.....	0
Hazardous substances / non hazardous pollutants:	-	
	Acrylamide.....	
	Benzene.....	
	Chlorinated solvents.....	
	Formaldehyde.....	
	Organometallics.....	
	Phenol.....	
	Styrene.....	
	Tri-butyl phosphate.....	
	Other organophosphates.....	

WASTE STREAM**7D40 ILW PCD Ion Exchange Resin**

Vinyl chloride.....

Arsenic.....

Barium.....

Boron..... P

Weighted Average over the entire inventory is 16.5 mg/l.

Cadmium.....

Caesium.....

Selenium.....

Chromium.....

Molybdenum.....

Thallium.....

Tin.....

Vanadium.....

Mercury compounds.....

Others.....

Electronic Electrical Equipment (EEE)

EEE Type 1.....

EEE Type 2.....

EEE Type 3.....

EEE Type 4.....

EEE Type 5.....

Complexing agents (%wt):

Yes

EDTA..... ~0.06

Weighted Average

DPTA.....

NTA.....

Polycarboxylic acids.....

Other organic complexants..... <2.5

Picolinate Acid present (~2.4 %mass) Formate Acid present (~0.09 %/mass)

Total complexing agents..... <2.5

LAW TREATMENT, PACKAGING AND DISPOSAL**Waste that is currently ILW:** The waste will become LLW as a result of radioactive decay. Waste may be treated to remove C14 and chelate content

WASTE STREAM 7D40 ILW PCD Ion Exchange Resin

Planned on-site / off-site treatments(s):

Treatment	On-site / Off site	Stream volume %
Low force compaction	Off-site	100.0
Supercompaction (HFC)		
Incineration		
Solidification		
Decontamination		
Metal treatment	On-site	100.0
Size reduction		
Decay storage		
Recycling / reuse		
Other / various		
None		

Comment on planned treatments:

When decayed to LLW (see 7D34 waste stream), the waste will require to be pre-treated to remove C-14 and also to destroy the chelates within the resin. Process yet to be agreed.

Disposal Routes:

Disposal Route	Stream volume %
Expected to be consigned to the LLW Repository	100.0
Expected to be consigned to a Landfill Facility	
Expected to be consigned to an On-Site Disposal Facility	
Expected to be consigned to an Incineration Facility	
Expected to be consigned to a Metal Treatment Facility	
Expected to be consigned as Out of Scope	
Expected to be recycled / reused	
Disposal route not known	

Upcoming (2019/20-2021/22) waste routing (if expected to change from above)

Disposal Route	Stream volume %		
	2019/20	2020/21	2021/22
Expected to be consigned to the LLW Repository			
Expected to be consigned to a Landfill Facility			
Expected to be consigned to an On-Site Disposal Facility			
Expected to be consigned to an Incineration Facility			
Expected to be consigned to a Metal Treatment Facility			
Expected to be consigned as Out of Scope			
Expected to be recycled / reused			
Disposal route not known			

Waste Packaging for Disposal:

Container	Stream volume %	Waste loading m ³	Number of packages
1/3 Height IP-1 ISO	100.0	~4	3
2/3 Height IP-2 ISO			
1/2 Height WAMAC IP-2 ISO			
1/2 Height IP-2 Disposal/Re-usable ISO			
2m box (no shielding)			
4m box (no shielding)			
Other			

Other information:

Encapsulated resin direct into HHISO or within 205 litre drums. These are loaded into HHISO containers for disposal. Alternative may be considered depending on the conditioning/treatment option used.

Waste Consigned to the LLW Repository:

Container voidage: <10%.

WASTE STREAM**7D40 ILW PCD Ion Exchange Resin**

Waste Characterisation Form (WCH):

The waste does not meet the LLWR's Waste Acceptance Criteria (WAC).

Waste consigned for disposal to LLWR in year of generation:

No. Decay storage periods could be up to 30 years for the Co-60 to decay. There is also an issue with high C-14. Waste stream will be conditioned/treated to ensure compliance with WAC. This may enable early disposal due to release of C-14 activity.

Potential for the waste to contain discrete items:

No

Non-Containerised Waste for In-Vault Grouting: (Not applicable to this waste stream)

Stream volume (%):

-

Waste stream variation:

-

Bounding cuboidal volume:

Inaccessible voidage:

-

Other information:

-

RADIOACTIVITY

Source:

Activation products that have been removed from the primary circuit during plant decontamination. The soluble activation products are removed by ion exchange material.

Uncertainty:

Activity for the major nuclides is determined by sampling and radiochemical analysis. The total specific activity should therefore be within $\pm 50\%$.

Definition of total alpha and total beta/gamma:

Where totals are shown on the table of radionuclide activities they are the sums of the listed alpha or beta/gamma emitting radionuclides plus 'other alpha' or 'other beta/gamma'.

Measurement of radioactivities:

Core samples are taken from each resin container. The sample is prepared and analysed to determine the major nuclides by gamma spectroscopy and other selective chemical techniques for other beta/gamma nuclides. Gross alpha and gross beta measurements are also taken. If certain trigger nuclides (e.g. Cs-137) are detected then additional analysis will be undertaken for other nuclides (e.g. I-129).

Other information:

The above activity information is considered to be bounding. MoD driven project has been set up to identify disposal option. Disposal planned within next 4-5 yrs i.e. before 2025.

WASTE STREAM

7D40 ILW PCD Ion Exchange Resin

Nuclide	Mean radioactivity, TBq/m ³				Nuclide	Mean radioactivity, TBq/m ³			
	Waste at 1.4.2019	Bands and Code	Future arisings	Bands and Code		Waste at 1.4.2019	Bands and Code	Future arisings	Bands and Code
H 3	4.33E-04	BB 1	~4.33E-04	BB 2	Gd 153				
Be 10					Ho 163				
C 14	8.72E-04	BB 1	~8.72E-04	BB 2	Ho 166m				
Na 22					Tm 170				
Al 26					Tm 171				
Cl 36					Lu 174				
Ar 39					Lu 176				
Ar 42					Hf 178n				
K 40					Hf 182				
Ca 41					Pt 193				
Mn 53					Tl 204				
Mn 54	6.74E-05	BB 1	~6.74E-05	BB 2	Pb 205				
Fe 55	8.45E-02	BB 1	~8.45E-02	BB 2	Pb 210				
Co 60	3.91E-02	BB 1	~3.91E-02	BB 2	Bi 208				
Ni 59					Bi 210m				
Ni 63	3.17E-03	BB 1	~3.17E-03	BB 2	Po 210				
Zn 65	3.9E-08	BB 1	~3.9E-08	BB 2	Ra 223				
Se 79					Ra 225				
Kr 81					Ra 226				
Kr 85					Ra 228				
Rb 87					Ac 227				
Sr 90					Th 227				
Zr 93					Th 228				
Nb 91					Th 229				
Nb 92					Th 230				
Nb 93m					Th 232				
Nb 94					Th 234				
Mo 93					Pa 231				
Tc 97					Pa 233				
Tc 99					U 232				
Ru 106					U 233				
Pd 107					U 234				
Ag 108m					U 235				
Ag 110m	1.74E-10	BB 1	~1.74E-10	BB 2	U 236				
Cd 109					U 238				
Cd 113m					Np 237				
Sn 119m					Pu 236				
Sn 121m					Pu 238				
Sn 123					Pu 239				
Sn 126					Pu 240				
Sb 125	8.45E-07	BB 1	~8.45E-07	BB 2	Pu 241				
Sb 126					Pu 242				
Te 125m					Am 241				
Te 127m					Am 242m				
I 129					Am 243				
Cs 134					Cm 242				
Cs 135					Cm 243				
Cs 137	6.40E-06	BB 1	~6.40E-06	BB 2	Cm 244				
Ba 133					Cm 245				
La 137					Cm 246				
La 138					Cm 248				
Ce 144					Cf 249				
Pm 145					Cf 250				
Pm 147					Cf 251				
Sm 147					Cf 252				
Sm 151					Other a	~1.06E-07	BB 2	~1.06E-07	BB 2
Eu 152					Other b/g	1.26E-08	BB 1	~1.26E-08	BB 2
Eu 154					Total a	~1.06E-07	BB 2	~1.06E-07	BB 2
Eu 155					Total b/g	1.28E-01	BB 1	~1.28E-01	BB 2

Bands (Upper and Lower)

- A a factor of 1.5
- B a factor of 3
- C a factor of 10
- D a factor of 100
- E a factor of 1000

Note: Bands quantify uncertainty in mean radioactivity.

Code

- 1 Measured activity
- 2 Derived activity (best estimate)
- 3 Derived activity (upper limit)
- 4 Not present
- 5 Present but not significant
- 6 Likely to be present but not assessed
- 7 Present in significant quantities but not determined
- 8 Not expected to be present in significant quantity