

WASTE STREAM	2X31	Solid LLW from Oxide Flask Maintenance Facility and Railways
---------------------	-------------	---

SITE Sellafield

SITE OWNER Nuclear Decommissioning Authority

WASTE CUSTODIAN Sellafield Limited

WASTE TYPE LLW

Is the waste subject to Scottish Policy: No

WASTE VOLUMES

		Reported
Stocks:	At 1.4.2022.....	0 m ³
Future arisings -	1.4.2022 - 31.3.2023.....	107.2 m ³
	1.4.2023 - 31.3.2024.....	140.1 m ³
	1.4.2024 - 31.3.2025.....	641.1 m ³
	1.4.2025 - 31.3.2026.....	588.2 m ³
	1.4.2026 - 31.3.2027.....	118.2 m ³
	1.4.2027 - 31.3.2028.....	118.2 m ³
	1.4.2028 - 31.3.2029.....	118.2 m ³
	1.4.2029 - 31.3.2030.....	118.2 m ³
	1.4.2030 - 31.3.2031.....	118.2 m ³
	1.4.2031 - 31.3.2032.....	118.2 m ³
	1.4.2032 - 31.3.2033.....	118.2 m ³
	1.4.2033 - 31.3.2034.....	118.2 m ³
	1.4.2034 - 31.3.2035.....	118.2 m ³
	1.4.2035 - 31.3.2036.....	118.2 m ³
	1.4.2036 - 31.3.2037.....	118.2 m ³
	1.4.2037 - 31.3.2038.....	118.2 m ³
	1.4.2038 - 31.3.2039.....	118.2 m ³
	1.4.2039 - 31.3.2040.....	118.2 m ³
	1.4.2040 - 31.3.2041.....	118.2 m ³
	1.4.2041 - 31.3.2042.....	118.2 m ³
	1.4.2042 - 31.3.2043.....	118.2 m ³
	1.4.2043 - 31.3.2044.....	118.2 m ³
Total future arisings:		3603.4 m ³
Total waste volume:		3603.4 m ³
Comment on volumes:	Arisings are sourced from REM_TP_0116A and are based on the latest five-year forecasts from the Waste Forecasting database. The overall timescale for waste arising are informed by the Sellafield Site Master Timeline. Uncertainty information is notional.	
Uncertainty factors on volumes:	Stock (upper): x	Arisings (upper) x 1.5
	Stock (lower): x	Arisings (lower) x 0.5

WASTE SOURCE The waste arises from care and maintenance of the facility. The facility is to be refurbished to repurpose the facility to enable acceptance of additional flasks in the future. This waste stream also covers waste generated by transportation logistics from the railway lines and the Railways Monitoring facility.

PHYSICAL CHARACTERISTICS

General description: The wastes are mostly secondary wastes and also some metallic wastes and hard wastes from excavations. The waste has not undergone any changes since it was generated.

Physical components (%wt): Metals (33.9%), Concrete/Rubble (32.3%), Soil (1%), Wood (2%), Rubber (1%), Halogenated Plastics (21.4%), Non-Halogenated Plastics (5.4%), Hydrocarbons (0.6%), and Asbestos (2.4%)

Sealed sources: The waste does not contain sealed sources.

Bulk density (t/m³): 1.153

Comment on density: The total Bulk density is derived from REM_TP_0116A and is based on lifetime mass and volume

CHEMICAL COMPOSITION

WASTE STREAM	2X31	Solid LLW from Oxide Flask Maintenance Facility and Railways
---------------------	-------------	---

General description and components (%wt): Metals (33.9%), Concrete/Rubble (32.3%), Soil (1%), Wood (2%), Rubber (1%), Halogenated Plastics (21.4%), Non-Halogenated Plastics (5.4%), Hydrocarbons (0.6%), and Asbestos (2.4%).

Chemical state: Neutral

Chemical form of radionuclides: -

Metals and alloys (%wt): Metal thickness not specified.

	(%wt)	Type(s) / Grade(s) with proportions	% of total C14 activity
Stainless steel.....	4.3		
Other ferrous metals.....	21.4		
Iron.....	3.2		
Aluminium.....	2.1		
Beryllium.....	0		
Cobalt.....	0		
Copper.....	0.86		
Lead.....	1.7		
Magnox/Magnesium.....	0		
Nickel.....	0		
Titanium.....	0		
Uranium.....	0		
Zinc.....	0.32		
Zircaloy/Zirconium.....	0		
Other metals.....	0		

Organics (%wt): -

	(%wt)	Type(s) and comment	% of total C14 activity
Total cellulose.....	2.0		
Paper, cotton.....	0		
Wood.....	2.0		
Halogenated plastics	21.4		
Total non-halogenated plastics.....	5.4		
Condensation polymers.....			
Others.....			
Organic ion exchange materials....	0		
Total rubber.....	1.0		
Halogenated rubber			
Non-halogenated rubber.....			
Hydrocarbons.....	0.59		
Oil or grease	0.27		
Fuel.....	0		
Asphalt/Tarmac (cont.coal tar)...	0.11		
Asphalt/Tarmac (no coal tar)....	0.11		
Bitumen.....	0.11		
Others.....	0		

WASTE STREAM	2X31	Solid LLW from Oxide Flask Maintenance Facility and Railways
---------------------	-------------	---

Other organics.....	0		
Other materials (%wt):	-		
	(%wt)	Type(s) and comment	% of total C14 activity
Inorganic ion exchange materials..	0		
Inorganic sludges and flocs.....	0		
Soil.....	1.0		
Brick/Stone/Rubble.....	32.3		
Cementitious material.....	0		
Sand.....	0		
Glass/Ceramics.....	0.05		
Graphite.....	0		
Desiccants/Catalysts.....	0		
Asbestos.....	2.4		
Non/low friable.....	0.11		
Moderately friable.....	0.11		
Highly friable.....	2.1		
Free aqueous liquids.....	0		
Free non-aqueous liquids.....	0		
Powder/Ash.....	0		
Inorganic anions (%wt):	-		
	(%wt)	Type(s) and comment	
Fluoride.....	0		
Chloride.....	0		
Iodide.....	0		
Cyanide.....	0		
Carbonate.....	0		
Nitrate.....	0		
Nitrite.....	0		
Phosphate.....	0		
Sulphate.....	0		
Sulphide.....	0		
Materials of interest for waste acceptance criteria:	-		
	(%wt)	Type(s) and comment	
Combustible metals.....	0		
Low flash point liquids.....	0		
Explosive materials.....	0		
Phosphorus.....	0		
Hydrides.....	0		
Biological etc. materials.....	0		
Biodegradable materials.....	0		

WASTE STREAM	2X31	Solid LLW from Oxide Flask Maintenance Facility and Railways	
---------------------	-------------	---	--

Putrescible wastes.....	0	
Non-putrescible wastes.....	0	
Corrosive materials.....	0	
Pyrophoric materials.....	0	
Generating toxic gases.....	0	
Reacting with water.....	2.5	Aluminium and Zinc
Higher activity particles.....	0	
Soluble solids as bulk chemical compounds.....	0	

Hazardous substances /
non hazardous pollutants: -

	(%wt)	Type(s) and comment
Acrylamide.....	0	
Benzene.....	0	
Chlorinated solvents.....	0	
Formaldehyde.....	0	
Organometallics.....	0	
Phenol.....	0	
Styrene.....	0	
Tri-butyl phosphate.....	0	
Other organophosphates.....	0	
Vinyl chloride.....	0	
Arsenic.....	0	
Barium.....	0	
Boron.....	0	
Boron (in Boral).....	0	
Boron (non-Boral).....	0	
Cadmium.....	0	
Caesium.....	0	
Selenium.....	0	
Chromium.....	0	
Molybdenum.....	0	
Thallium.....	0	
Tin.....	0	
Vanadium.....	0	
Mercury compounds.....	0	
Others.....	0	
Electronic Electrical Equipment (EEE)		
EEE Type 1.....		17 Items in 3 years.
EEE Type 2.....		
EEE Type 3.....		30 Items in 3 years.
EEE Type 4.....		30 Items in 3 years.

WASTE STREAM**2X31****Solid LLW from Oxide Flask Maintenance Facility and Railways**

EEE Type 5.....

Complexing agents (%wt): Yes

	(%wt)	Type(s) and comment
EDTA.....	<0.01	
DPTA.....	0	
NTA.....	0	
Polycarboxylic acids.....	0	
Other organic complexants.....	0	
Total complexing agents.....	<0.01	

Potential for the waste to contain discrete items: Yes. Lead bricks, sheets, steel channels, hand tool.

TREATMENT, PACKAGING AND DISPOSAL

Planned on-site / off-site treatment(s):

Treatment	On-site / Off site	Stream volume %
Low force compaction		
Supercompaction (HFC)	On-site	6.6
Incineration	Off-site	14.6
Solidification		
Decontamination		
Metal treatment	Off-site	1.2
Size reduction		
Decay storage		
Recycling / reuse		
Other / various		
None		77.6

Comment on planned treatments:

All high force compaction takes place in WAMAC. For Inventory purposes, it is assumed that supercompaction will continue after the closure of WAMAC in 2028. Waste not requiring treatment is VLLW, direct disposal to LLWR and 'out of scope' metal.

Disposal Routes:

Disposal Route	Stream volume %	Disposal density t/m3
Expected to be consigned to the LLW Repository	9.7	0.48
Expected to be consigned to a Landfill Facility		
Expected to be consigned to an On-Site Disposal Facility	26.9	1.5
Expected to be consigned to an Incineration Facility	14.6	0.14
Expected to be consigned to a Metal Treatment Facility	1.2	1.4
Expected to be consigned as Out of Scope	47.6	1.4
Expected to be recycled / reused		
Disposal route not known		

Classification codes for waste expected to be consigned to a landfill facility: -

Upcoming (2022/23-2024/25) Waste Routing (if expected to change from above):

WASTE STREAM**2X31****Solid LLW from Oxide Flask Maintenance Facility and Railways**

Disposal Route	Stream volume %		
	2022/23	2023/24	2024/25
Expected to be consigned to the LLW Repository	13.2	9.9	4.9
Expected to be consigned to a Landfill Facility			
Expected to be consigned to an On-Site Disposal Facility	10.5	11.4	73.4
Expected to be consigned to an Incineration Facility	2.3	15.9	0.35
Expected to be consigned to a Metal Treatment Facility			
Expected to be consigned as Out of Scope	74.0	62.8	21.3
Expected to be recycled / reused			
Disposal route not known			

Opportunities for alternative disposal routing: No

Baseline Management Route	Opportunity Management Route	Stream volume (%)	Estimated Date that Opportunity will be realised	Opportunity Confidence	Comment
-	-	-	-	-	-

Waste Packaging for Disposal:

Container	Stream volume %	Waste loading m ³	Number of packages
1/3 Height IP-1 ISO			
2/3 Height IP-2 ISO			
1/2 Height WAMAC IP-2 ISO	6.6	59.28	5
1/2 Height IP-2 Disposal/Re-usable ISO	3.1	10	12
2m box (no shielding)			
4m box (no shielding)			
Other (VLLW Disposed on site - No packages)	26.9		

Other information: -

Waste Planned for Disposal at the LLW Repository:

Container voidage: -

Waste Characterisation Form (WCH): The waste meets the LLWR's Waste Acceptance Criteria (WAC). The waste has a current WCH. Differences exist between Inventory information and current WCH. Materials and radioactivity data have been taken from the current WCH, but data on waste volumes and waste routes are based on the Waste Forecasting database as this information is more recent.

Waste consigned for disposal to LLWR in year of generation: Yes.

Non-Containerised Waste for In-Vault Grouting: (Not applicable to this waste stream)

Stream volume (%): -

Waste stream variation: -

Bounding cuboidal volume:

Inaccessible voidage: -

Other information: -

RADIOACTIVITY

Source: The activity arises as a result of operations to decontaminate flasks and originates from the fuels these flasks were used to transport.

Uncertainty: The uncertainty associated with the derived fingerprint is likely to be relatively low, however

WASTE STREAM**2X31****Solid LLW from Oxide Flask Maintenance Facility and Railways**

Definition of total alpha and total beta/gamma:	the volumes and total activity information (and possibly some other assumptions) are likely to be more notional and thus more uncertain. Where totals are shown on the table of radionuclide activities they are the sums of the listed alpha or beta/gamma emitting radionuclides plus 'other alpha' or 'other beta/gamma'.
Measurement of radioactivities:	Specific activity data is based on data in the corresponding WCH, which in turn maps an estimated total activity to a derived radionuclide fingerprint (which has been derived based on the fingerprints of the donor areas and weighted by the number of flasks expected to be consigned from each area).
Other information:	The radionuclides have been taken from REM_TP_0116A and are based on the current WCH.

WASTE STREAM

2X31

Solid LLW from Oxide Flask Maintenance Facility and Railways

Nuclide	Mean radioactivity, TBq/m ³				Nuclide	Mean radioactivity, TBq/m ³			
	Waste at 1.4.2022	Bands and Code	Future arisings	Bands and Code		Waste at 1.4.2022	Bands and Code	Future arisings	Bands and Code
H 3			1.36E-07	CC 2	Gd 153				
Be 10					Ho 163				
C 14			2.84E-08	CC 2	Ho 166m				
Na 22					Tm 170				
Al 26					Tm 171				
Cl 36					Lu 174				
Ar 39					Lu 176				
Ar 42					Hf 178n				
K 40					Hf 182				
Ca 41					Pt 193				
Mn 53					Tl 204				
Mn 54			3.70E-09	CC 2	Pb 205				
Fe 55			6.02E-07	CC 2	Pb 210				
Co 60			1.85E-06	CC 2	Bi 208				
Ni 59					Bi 210m				
Ni 63			6.25E-07	CC 2	Po 210				
Zn 65					Ra 223				
Se 79					Ra 225				
Kr 81					Ra 226				
Kr 85					Ra 228				
Rb 87					Ac 227				
Sr 90			1.16E-06	CC 2	Th 227				
Zr 93					Th 228		1.07E-11	CC 2	
Nb 91					Th 229				
Nb 92					Th 230				
Nb 93m					Th 232				
Nb 94					Th 234				
Mo 93					Pa 231				
Tc 97					Pa 233				
Tc 99			7.41E-09	CC 2	U 232				
Ru 106					U 233				
Pd 107					U 234		1.23E-09	CC 2	
Ag 108m					U 235		1.23E-10	CC 2	
Ag 110m					U 236		1.85E-11	CC 2	
Cd 109					U 238		2.47E-09	CC 2	
Cd 113m					Np 237				
Sn 119m					Pu 236				
Sn 121m					Pu 238		6.91E-08	CC 2	
Sn 123					Pu 239		5.31E-08	CC 2	
Sn 126					Pu 240		6.54E-08	CC 2	
Sb 125			4.94E-09	CC 2	Pu 241		2.73E-06	CC 2	
Sb 126					Pu 242		2.15E-11	CC 2	
Te 125m					Am 241		1.52E-07	CC 2	
Te 127m					Am 242m				
I 129					Am 243				
Cs 134			5.43E-08	CC 2	Cm 242		6.17E-10	CC 2	
Cs 135					Cm 243		5.21E-12	CC 2	
Cs 137			4.36E-06	CC 2	Cm 244		9.87E-09	CC 2	
Ba 133					Cm 245				
La 137					Cm 246				
La 138					Cm 248				
Ce 144			8.64E-09	CC 2	Cf 249				
Pm 145					Cf 250				
Pm 147			3.20E-07	CC 2	Cf 251				
Sm 147					Cf 252				
Sm 151			4.57E-08	CC 2	Other a				
Eu 152					Other b/g		1.23E-09	CC 2	
Eu 154			2.47E-08	CC 2	Total a	0	3.54E-07	CC 2	
Eu 155			3.09E-08	CC 2	Total b/g	0	1.20E-05	CC 2	

Bands (Upper and Lower)

- A a factor of 1.5
- B a factor of 3
- C a factor of 10
- D a factor of 100
- E a factor of 1000

Note: Bands quantify uncertainty in mean radioactivity.

Code

- 1 Measured activity
- 2 Derived activity (best estimate)
- 3 Derived activity (upper limit)
- 4 Not present
- 5 Present but not significant
- 6 Likely to be present but not assessed
- 7 Present in significant quantities but not determined
- 8 Not expected to be present in significant quantity